

Product Information

USB Charging Unit

Compact charging solutions for passenger areas



USB Charging Unit – Compact charging solutions with system compatibility

SBF offers configurable USB components consisting of an interface and a DC-DC converter. Integration is tailored to the installation location and interface type – flexible, spacesaving and system-compatible.

The interface is available in various versions (USB A and USB C) and can be configured with 1, 2 or 4 ports. The DC converter ensures stable power supply (110 V DC input / up to 65 W via USB PD 3.0) and supports modern charging functions such as PPS.

Advantages at a glance

- Standard components flexibly applicable
- 1-port, 2-port or 4-port configuration
- Interfaces: USB A and USB C
- Components compliant with EN45545, EN50155, EN50121 and EN61373

Technical Specifications

- Integration depending on installation location and mechanical interface
- Input voltage: 110 V DC ±25 %
- Output power: up to 65 W
- With PPS function

Für detaillierte technische Informationen und individuelle Ausführungen stehen wir Ihnen gerne zur Verfügung.




USB interface / USB A - USB C

Example installation situation and housing



DC-DC converter

Detailed view of converter components



Are you interested in more SBF products?

Then contact us:

www.sbf-germany.com/en/kontakt

or by e-mail at info@sbf-germany.com

All information and technical details on our other solutions can be found in our download area: www.sbf-germany.com/en/downloads



Luggage RacksProduct Information



LED Light ProfilesProduct Information



Air Duct Systems
Product Information



LED Standard SpotsProduct Information



Fiber-Optic Guides
Product Information